

Pneumatic

Hochdruck-Polyethylen-Schlauch (PE) natur

Temperaturen -20° C bis + 40° C

Nennmaße in mm		Wandstärke	zul. Druck	Art.-Nr.	€/100 m
Ø Außen	Ø Innen	mm	kp/cm² bei 20° C		
6	4	1	13 bar	30.325.004	28,10
8	6	1	8 bar	30.325.005	37,75
10	8	1	8 bar	30.325.008	49,70
12	10	1	5 bar	30.325.011	63,25



Hochdruck Polyamid-Schlauch (PA) natur

Temperaturen -40° C bis + 90° C

Nennmaße in mm		Wandstärke	zul. Druck	Art.-Nr.	€/100 m
Ø Außen	Ø Innen	mm	kp/cm² bei 20° C		
6	4	1	27 bar	30.326.007	112,30
8	6	1	19 bar	30.326.008	156,85



Winkelverschraubung drehbar

Gewinde	Schlauch	Art.-Nr.	€/100 m
1/8"	6/4		
1/8"	8/6	33.322.002	2,45
1/4"	6/4	33.322.003	2,65
1/4"	8/6	33.322.004	2,70



T-Verschraubung drehbar

Gewinde	Schlauch	Art.-Nr.	€/100 m
1/8"	6/4		
1/8"	8/6	33.323.002	2,85
1/4"	6/4	33.323.003	3,05
1/4"	8/6	33.323.004	3,10



Gerade Einschraubverschraubung mit Mutter

Gewinde	Schlauch	Art.-Nr.	€/100 m
1/8"	6/4		
1/8"	8/6	33.329.002	0,60
1/4"	6/4	33.329.003	0,70
1/4"	8/6	33.329.004	0,70



3-fach-Verteiler

Schlauch	Art.-Nr.	€/100 m
6 - 4		
8 - 6	33.324.002	1,80



Aluschraube

Gewinde	Art.-Nr.	€/100 m
1/8"		
1/4"	33.326.117	1,80

